

TORC | TECH

Hydraulic Torque Wrenches

Basınç - Tork Dönüşüm Tablosu

TW-H

BASINÇ	TORK NM		BASINÇ	TORK NM	
BAR	19-46 mm	50-60 mm	BAR	19-46 mm	50-60 mm
70	262	306	390	1460	1705
80	299	350	400	1497	1749
90	337	393	410	1535	1792
100	374	437	420	1572	1836
110	412	481	430	1609	1880
120	449	525	440	1647	1923
130	487	568	450	1684	1967
140	524	612	460	1722	2011
150	561	656	470	1759	2055
160	599	699	480	1797	2098
170	636	743	490	1834	2142
180	674	787	500	1871	2186
190	711	831	510	1909	2229
200	749	874	520	1946	2273
210	786	918	530	1984	2317
220	823	962	540	2021	2361
230	861	1005	550	2059	2404
240	898	1049	560	2096	2448
250	936	1093	570	2133	2492
260	973	1137	580	2171	2535
270	1011	1180	590	2208	2579
280	1048	1224	600	2246	2623
290	1085	1268	610	2283	2667
300	1123	1311	620	2321	2710
310	1160	1355	630	2358	2754
320	1198	1399	640	2395	2798
330	1235	1443	650	2433	2841
340	1273	1486	660	2470	2885
350	1310	1530	670	2508	2929
360	1347	1574	680	2545	2973
370	1385	1617	690	2583	3016
380	1422	1661	700	2625	3068



TW-H27

ISO 9001: 2015 DS:TW-H-TC0125-TR

Basınç-tork tablosundaki veriler, fabrika kalibrasyon doğrulama değerlerini temsil etmektedir.

www.torc-tech.com info@torc-tech.com

A Brand of Surkon International