



Standart Seri Havalı Tork Artırıcılar

Standard Series Pneumatic Torque Multipliers



- » Cihaz kapasitesinin %20-%100 aralığında \pm %5 hassasiyet.
- » Fabrika çıkışlı, seri numaralı izlenebilir kalibrasyon belgesi.
- » Dakikada 150 rpm'e kadar boşta dönüş hızı.
- » İki hızlı şanzıman seçeneği sayesinde daha hızlı işlem.
- » Saniyede 19 litre hava tüketimi, 5 bar çalışma basıncı.
- » Uzun ömürlü sağlam ve hafif yapı, hızlı ve kolay kullanım.
- » Darbesiz, sessiz, çalışma gürültüsü 85 dB(A) altındadır.

- » \pm %5 repeatability of reading from 20% to 100% of range.
- » Serial number and calibration certificate for each tool.
- » Maximum idle speed 150 rpm.
- » Available with manual or automatic two speed gearbox.
- » Maximum working pressure 5 bar, air consumption 19 litres/sec.
- » Robust and lightweight, quick and easy to operate
- » Quiet - less than 85 dB(A) when under load.

Parça Part	Kapasite Capacity		Sürücü Sq. Drive	Devir Hızı Idle Speed	Ağırlık Weight	D	H	L	R2 min	R2 max
No.	N.m	Lbf.ft	inç	d/d (rpm)	kg	mm				
Tek Hızlı Hafif İş Havalı Tork Artırıcılar / Single Speed Pneumatic Torque Multipliers										
16031	160 - 680	120 - 500	3/4"	30	12.8	108	350	303	83	216
16011	160 - 680	120 - 500	1"	30	12.8	108	350	303	83	216
16098	270 - 1.200	200 - 900	3/4"	15	13.3	108	350	303	83	216
16097	270 - 1.200	200 - 900	1"	15	13.3	108	350	303	83	216
16013	515 - 1.700	380 - 1.250	1"	9	13.3	108	350	303	83	216
16015	880 - 3.400	650 - 2.500	1"	5	16.5	119	393	355	86	263
16017	880 - 3.400	650 - 2.500	1.1/2"	5	16.5	119	395	355	86	263
Otomatik İki Hızlı Hafif İş Havalı Tork Artırıcılar / Automatic Two Speed Pneumatic Torque Multipliers										
16031.AUT	160 - 680	120 - 500	3/4"	150	16.3	108	419	303	83	216
16011.AUT	160 - 680	120 - 500	1"	150	16.3	108	419	303	83	216
16098.AUT	400 - 1.200	295 - 900	3/4"	75	16.8	108	419	303	83	216
16097.AUT	400 - 1.200	295 - 900	1"	75	16.8	108	419	303	83	216
16013.AUT	700 - 1.700	516 - 1.250	1"	45	16.8	108	419	303	83	216
16015.AUT	880 - 3.400	650 - 2.500	1"	25	20	119	462	355	86	263
16017.AUT	880 - 3.400	650 - 2.500	1.1/2"	25	20	119	464	355	86	263
Manuel İki Hızlı Hafif İş Havalı Tork Artırıcılar / Manual Two Speed Pneumatic Torque Multipliers										
16031.MTS	160 - 680	120 - 500	3/4"	150	16.3	108	436	303	83	216
16011.MTS	160 - 680	120 - 500	1"	150	16.3	108	436	303	83	216
16098.MTS	270 - 1.200	200 - 900	3/4"	75	16.8	108	436	303	83	216
16097.MTS	270 - 1.200	200 - 900	1"	75	16.8	108	436	303	83	216
16013.MTS	515 - 1.700	380 - 1.250	1"	45	16.8	108	436	303	83	216
16015.MTS	880 - 3.400	650 - 2.500	1"	25	20	119	479	355	86	263
16017.MTS	880 - 3.400	650 - 2.500	1.1/2"	25	20	119	481	355	86	263

