

## 2640D / 2640N – Ultra-high pressure water jetting hose



Ultra-high pressure

### APPLICATIONS

- Ultra-high pressure service for the construction and shipbuilding industries and for general industrial cleaning applications.
- Mainly used for hydrodemolition and removal of accumulated dirt and materials from surfaces such as concrete, asphalt and tanks.
- For use with petroleum or synthetic hydraulic fluids, gas and chemical fluids. Especially suitable for hydraulic pre-tensioning equipment, test rigs, as well as in offshore oil applications.

### CONSTRUCTION

**Core tube** : DN 4-8: Polyoxymethylene; DN 12-25: Polyamide  
**Pressure reinforcement** : Six spiral layers of maximum tensile steel wire

**Cover** : Polyamide  
**Colour** : Blue

### TEMPERATURE RANGE

-10°C up to +70°C

#	Ø				Ø		Ø		Ø		Ø	
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m	
2640D-025V32	4	-025	3.9	5/32	12.0	280	40,600	700	101,500	140	0.29	
2640D-03V32	5	-03	4.7	3/16	13.0	250	36,250	625	90,625	175	0.41	
2640D-05V32	8	-05	8.0	5/16	16.9	210	30,450	525	76,125	225	0.68	
2640N-08V32	12	-08	12.8	1/2	24.5	180	26,100	450	65,250	290	1.36	
2640N-12V32	20	-12	19.6	3/4	33.0	140	20,300	350	50,750	350	2.10	
2640N-16V32	25	-16	25.0	1	40.0	120	17,400	300	43,500	400	2.90	

NOTES -