



## Darbeli Akülü Somun Sıkma-Sökme Tabancaları

Cordless Impact Wrenches [1/2" - 3/4"]



- » Sökme torku max. 260 - 1400 N.m
- » Sıkma torku max. 200 - 1000 N.m
- » Önerilen tork değeri 200 - 1000 N.m
- » Kare sürücü lokma girişi 1/2" - 3/4"
- » Düşük deşarj özellikli Li-ion pil
- » Motor devri 1800 - 2700 rpm
- » Gürültü seviyesi 99.4 - 101 dB(A)
- » Titreşimi aralığı 14.9 - 17.8 m/s<sup>2</sup>
- » Kalibrasyon belgeli, Menşei Almanya, Hazet
- » Türkiye'de servis ve yedek parça hizmeti

- » Loosening torque max. 260 - 1400 N.m
- » Tightening torque max. 200 - 1000 N.m
- » Recommended torque 200 - 1000 N.m
- » Square drive size 1/2" - 3/4"
- » Sound level 99.4 - 101 dB(A) LpA
- » Engine revolutions 1800 - 2700 rpm
- » Vibration acceleration 14.91 - 17.8 m/s<sup>2</sup>
- » Li-ion battery with very low self-discharge
- » Trade mark Hazet, manufactured in Taiwan

Özellikler Specifications	Birimler Units	9212 SPC	9212 M	9212	9212-1000	9213-1000
Sökme Torku/Torque Loos.	N.m	200	220	500	1000	1000
Sıkma Torku/Torque Tight.	N.m	260	270	700	1400	1400
Önerilen Tork/Recom. Torque	N.m	200	220	500	1000	1000
Kare Sürücü/Square Drive	inch	1/2"	1/2"	1/2"	1/2"	3/4"
Çalışma Gürültüsü/Sound	dB(A)	100	99.6	99.4	101	101
Titreşim Seviyesi/Vibration Acc.	m/s <sup>2</sup>	14.91	15.4	20.3	17.8	17.8
Saplama Ölçüsü/Stud Size	mm	M16	M16	M16	M24	M24
Lit-İon Akü/Lit-ion Battery	#	18V 5Ah	18V 5Ah	18V 5Ah	18V 5Ah	18V 5Ah
Motor Devri/Revolution	rpm	2700	2500	2000	1800	1800
Ebatlar/Sizes	mm	167 x 65 x 187	228 x 63 x 135	204 x 64 x 259	278 x 230 x 89.5	278 x 230 x 89.5
Ağırlık/Weight	kg	1.45	1.34	1.85	3.64	3.7

