

# Heavy Duty Wheels

Model SD ... S, K, S/P

■ Swivel castors - Drawing No. R7





## Range of application:

- For transporting loads at a maximum speed of 100 m/min.
- For turning corners.
- Frequently used on construction sites.



## Characteristics of the model ... SD:

- Solid steel construction of the rotating mountings.
- Can be combined with other castors.



## Model SD ... S, SD ... K

Mod.		a	b	c	∅ d1	∅ e	f	g	h	j	k	Suitable castors	Carrying capacity (kN)		Weight (kg)	
Steel	Plastic												S	K	S	K
SD 150 S	SD 150 K	220	150	190	150	14	115	15	210	80	120	SF	30	20	21.4	15.4
SD 175 S	SD 175 K	220	150	190	175	14	115	15	235	80	120	SF	30	20	26.2	16.9
SD 200 S	SD 200 K	220	150	190	200	14	115	15	260	80	120	SF	30	30	31.6	18.5
SD 225 S	SD 225 K	270	210	210	225	18	150	15	285	80	120	SF	30	30	40.4	22.9
SD 250 S	SD 250 K	270	210	210	250	18	150	15	310	80	120	SF	35	35	47.3	24.7
SD 275 S	SD 275 K	270	210	210	275	18	150	15	335	80	120	SF	35	35	55.2	26.5



## Model SD ... S/P

Mod.		a	b	c	∅ d1	∅ e	f	g	h	j	k	Suitable castors	Carrying capacity (kN)		Weight (kg)	
Steel																
SD 150 S/P		270	170	220	150	18	130	20	220	80	130	SF	50			21.6
SD 175 S/P		270	170	220	175	18	130	20	245	80	130	SF	50			26.4
SD 200 S/P		270	170	220	200	18	130	20	285	80	130	SF	60			31.8