



## HT30-60 İnce Gövde Mekanik Tork Arttırıcılar [300-6000 N.m]

HT30-60 Handtorque Torque Multipliers- [300-6000 N.m]



- » Torklama hassasiyeti  $\pm 4\%$ , **300-6000 N.m** 6 model
  - » Aktarım oranları 5:1 / 15:1 / 25:1 / 125:1
  - » Cihaz, sıkma ve sökme işlemlerine uygundur
  - » Ergonomik ve ince tasarım, küçük hacim
  - » Daraltılmış dış çap ile dar bölgelerde kullanım
  - » Kaydırmalı destek ayağı opsiyonel olarak sunulur
  - » Geri dönüş kilit mekanizması ile güvenli çalışma
  - » Akredite kalibrasyonlu olarak sipariş verilebilir
  - » Endüstriyel ağır iş uygulamaları için uygun tasarım
  - » Türkiye'de garanti servis ve yedek parça hizmeti
- 
- » Accuracy guaranteed better than  $\pm 4\%$ ,
  - » 5:1 / 15:1 / 25:1 / 125:1 torque multiplication
  - » 6 different models between 300-6000 N.m
  - » Suitable for clockwise and counter clockwise
  - » Small, compact and aesthetics desing
  - » Reduced diameter enables better access
  - » Robust construction, dont need maintenance
  - » Anti Wind-Up Ratchet (AWUR) fitted to allow safer
  - » Heavy duty is ideal for inclusion in the tool kit
  - » UKAS accredited calibration may be ordered

Parça Part	Tork Aralığı Torque Range		Oran Ratio	Kilit Locked	Giriş Kare Input Square	Çıkış Kare Output Square	Ağırlık Weight	Ölçüler (mm) Sizes				
	#	N.m						lbf.ft	#	#	inch	inch
18003	300-3000	220-2200	5:1	-	3/4"	1"	5.0	164	60	88	117	140
18004	300-3000	220-2200	15:1	AWUR	1/2"	1"	7.0	183	60	88	117	140
18006	300-3000	220-2200	25:1	AWUR	1/2"	1"	7.0	183	60	88	117	140
18009	600-6000	440-4400	25:1	-	1/2"	1.1/2"	9.5	212	94	119	146	174
18008	600-6000	440-4400	25:1	AWUR	1/2"	1.1/2"	10.6	218	94	119	146	174
18013	600-6000	440-4400	125:1	-	1/2"	1.1/2"	11.0	240	94	119	146	174

AWUR işaretli ürünlerde geri dönüş kilit sistemi vardır. AWUR : Anti Wind Up Ratchet (Return Lock System).

