



## Değişken Uçlu Tork Anahtarları - [3 - 400 N.m]

Female Torque Handles Torque Wrenches - [3 - 400 N.m]



Sürücü/Drive: S7  
Spigot Uçlu Sürücü  
Spigot Torque Handle



Sürücü/Drive: S3  
Değişken Tip Dişi Sürücü  
Female Torque Handle

### Ayarlanabilir Spigot Uçlu Tork Anahtarları - [N.m - Lbf.ft]

Adjustable Spigot Torque Handle - Dual Scale - [N.m - Lbf.ft]

Parça Part	Tork Aralığı Torque Range			Sürücü Drive	Ağırlık Weight	Uzunluk Length
	#	N.m	lbf.in			
15060	3-15	27-132	*	16 - S7	0.3	223
15061	5-25	44-220	*	16 - S7	0.3	223
15062	10-50	*	7.5-37.5	16 - S7	0.6	322
15063	20-100	*	15-75	16 - S7	0.7	363
15064	40-200	*	30-150	16 - S7	0.9	445
15065	60-300	*	44-222	16 - S7	1.2	569

### Ayarlanabilir Spigot Uçlu Tork Anahtarları - [N.m]

Adjustable Female Torque Handle - N.m Scale Only

Parça Part	Tork Aralığı Torque Range			Sürücü Drive	Ağırlık Weight	Uzunluk Length
	#	N.m	lbf.in			
15070	3-15	*	*	16 - S7	0.3	223
15071	5-25	*	*	16 - S7	0.3	223
15072	10-50	*	*	16 - S7	0.6	322
15073	20-100	*	*	16 - S7	0.7	363
15074	40-200	*	*	16 - S7	0.9	445
15075	60-300	*	*	16 - S7	1.2	569

### Ayarlanabilir Değişken Uçlu Tork Anahtarları - [N.m - Lbf.ft]

Adjustable Female Torque Handle - Dual Scale - [N.m - Lbf.ft]

Parça Part	Tork Aralığı Torque Range			Sürücü Drive	Ağırlık Weight	Uzunluk Length
	#	N.m	lbf.in			
15100	3-15	27-132	*	9x12 - S3	0.3	218
15101	5-25	44-220	*	9x12 - S3	0.3	218
15102	10-50	*	7.5-37.5	9x12 - S3	0.6	325
15103	20-100	*	15-75	9x12 - S3	0.7	365
15104	40-200	*	30-150	9x12 - S3	0.9	442
15105	40-200	*	30-150	14x18 - S3	1.0	453
15106	60-300	*	44-222	14x18 - S3	1.2	570
15107	60-340	*	44-250	14x18 - S3	1.3	662
15108	80-400	*	60-300	14x18 - S3	1.7	664

### Ayarlanabilir Değişken Uçlu Tork Anahtarları - [N.m]

Adjustable Female Torque Handle - N.m Scale Only

Parça Part	Tork Aralığı Torque Range			Sürücü Drive	Ağırlık Weight	Uzunluk Length
	#	N.m	lbf.in			
15110	3-15	*	*	9x12 - S3	0.3	218
15111	5-25	*	*	9x12 - S3	0.3	218
15112	10-50	*	*	9x12 - S3	0.6	325
15113	20-100	*	*	9x12 - S3	0.7	365
15114	40-200	*	*	9x12 - S3	0.9	442
15115	40-200	*	*	14x18 - S3	1.0	453
15116	60-300	*	*	14x18 - S3	1.2	570
15117	60-340	*	*	14x18 - S3	1.3	662
15118	80-400	*	*	14x18 - S3	1.7	664

- » Torklama hassasiyeti  $\pm 3\%$
- » Tork aralığı **3 - 400 N.m**
- » Tork aralığı **7.5 - 300 Lbf.ft**
- » Tork aralığı **27- 220 Lbf.in**
- » ISO 6789-2:2017 ye uygun tasarım
- » Mikrometre göstegeli, kolay ayar
- » 72 diş ince ayar cırcır mekanizması
- » Kare sürücülü cırcır veya değişken uç seçeneği
- » Seri numaralı üretici fabrika kalibrasyon belgesi
- » Türkak akreditasyonlu kalibrasyon opsiyoneldir
- » Menşei İngiltere, üretici Norbar, CE sertifikalı
- » Servis ve kalibrasyon Surkon tarafından karşılanır

- » Torque accuracy  $\pm 3\%$
- » Torque ranges 3-400 N.m
- » Torque ranges 7.5 - 300 Lbf.ft
- » Torque ranges 27-220 Lbf.in
- » Meets the requirements of ISO 6789-1:2017
- » Micrometer Scale for error free setting
- » 3/4" 3/8" 1/2" SD ratchet
- » Delivered with Norbar house calibration certificate
- » Origin UK, manufactured by Norbar, CE certified

Kilit Açık/Unlocked

Kilitli/Locked

