



Yeni Nesil Havalı Tork Anahtarları

PTS Series Pneumatic Torque Multipliers



- » Cihaz kapasitesinin %20-%100 aralığında ± 5 hassasiyet.
- » Fabrika çıkışlı, seri numaralı izlenebilir kalibrasyon belgesi.
- » 100 ile 7.000 N.m arasında on farklı model.
- » Dakikada maksimum 35.5 rpm'e kadar dönüş hızı.
- » Saniyede 16.5 litre hava tüketimi, 6.5 bar çalışma basıncı.
- » Darbesiz, sessiz, çalışma gürültüsü 72-79 dB(A) aralığındadır.
- » Elde hissedilen titreşim seviyesi 2.5m/s^2 'nin altındadır.
- » Yön mandalı ile sıkma ve sökme yönüne kolayca geçiş sağlar.
- » PT serisi eşdeğerlerine göre yaklaşık 2.5 kg daha hafiftir.
- » PTM ve EvoTorque aksesuarlarıyla uyumludur.
- » Standart olarak çelik destek ayağı ile sevk edilir.

- » ± 5 repeatability of reading from 20% to 100% of range.
- » Serial number and calibration certificate for each tool.
- » Ten different model options from 100 - 7.000 N.m.
- » Maximum idle speed 35.5 rpm. 60% faster than PT-72 model.
- » Maximum working pressure 6.5 bar, air consumption 16.5 litres/sec.
- » Non impacting - low vibration levels, handle vibration $< 2.5\text{m/s}^2$.
- » Quiet - less than 79 dB(A) when under load.
- » Easily accessible switch for forward and reverse operation.
- » Up to 2.5kg weight saving compared with PT equivalents.
- » Compatible with PTM and EvoTorque accessories.
- » Steel reactions supplied as standard. Bespoke reactions available.

Parça Part	Kapasite Capacity		Şanzıman Çapı Gear Dia. (ØC)	Sürücü Sq. Drive	Devir Hızı Idle Speed	Ağırlık Weight	D	H1	H2	L	R1	R2 min	R2 max
No.	N.m	lbf.ft	mm	inç	d/d rpm	kg	mm						
180241.B06	100 - 500	74 - 370	52	3/4"	35.5	5.05	52	30	243	263	59	71	131
180242.B06	160 - 800	118 - 590	52	3/4"	25.7	5.05	52	30	243	263	59	71	131
180243.B06	200 - 1.000	147 - 738	72	3/4"	20.4	7.64	72	30	243	290	76	124	167
180244.B08	270 - 1.350	200 - 1.000	72	1"	14.7	7.64	72	30	243	290	76	124	167
180245.B08	400 - 2.000	295 - 1.475	72	1"	9.2	8	72	30	243	324	76	124	167
180246.B08	540 - 2.700	400 - 2.000	80	1"	7.3	7.55	80	30	243	290	76	124	167
180250.B08	800 - 4.000	590 - 2.950	92	1"	5.3	11.45	92	30	243	347	70	125	175
180250.B12	800 - 4.000	590 - 2.950	92	1.1/2"	5.3	11.45	92	30	243	347	70	125	175
180248.B12	1.200 - 6.000	885 - 4.425	119	1.1/2"	2.6	16.32	119	30	243	369	90	162	210
180249.B12	1.400 - 7.000	1.030 - 5.200	119	1.1/2"	2.6	16.32	119	30	243	369	90	162	210

