

Rehobot Tek Etkili Delikli Alüminyum Kriko

Single Acting Hollow Cylinders Aluminium



- » Kaldırma kapasite aralığı 13 – 103 ton
 - » Kaldırma kurs aralığı 51 – 153 mm
 - » Çalışma basıncı 700 – 800 bar
 - » Tek etkili, çelik, ortası delik silindir
 - » Alüminyum mamül, ortası delik silindir
 - » Çelik silindirlere göre %50 daha hafif
 - » İtme çekme işlemleri için uygun
 - » Her marka hidrolik pompaya uyumlu
 - » ISO9001- CE kalite belgesi imalat
 - » Menşei İsveç, Üretici REHOBOT
 - » Teknik destek Surkon tarafından sağlanır
-
- » Capacity from 13 to 103 tons
 - » Cylinder stroke 51 – 153 mm
 - » Working pressure 700 - 800 bar
 - » Single acting, spring acting
 - » Weight 50% less than steel cylinders
 - » Used for push and pull operations
 - » Compatible with all hydraulic pumps
 - » ISO9001- CE quality certified
 - » Origin Sweden, manufacturer Rehobot

Model Model	Ürün Kodu Part No	Kapasite Capacity	Strok Stroke	Delik Çapı Hole Dia.	Kapalı Boy Closed H.	Dış Çap Outer Dia.	Etki Alanı Effective A.	Yağ Hacmi Oil Volume	Ağırlık Weight
#	#	kN (Ton)	mm	Ø mm	mm	Ø mm	cm ²	cm ³	kg
CHFA132	45862	123 (13)	52	22	165	80	18	90	2.3
CHFA136	46602	123 (13)	153	22	310	80	18	270	4.0
CHFA182A	46621	176 (18)	51	26	171	94	25	125	3.0
CHFA184A	46622	176 (18)	102	26	246	94	25	250	4.0
CHFA262	46641	255 (26)	51	32	180	115	37	185	4.9
CHFA266	46642	255 (26)	153	32	323	115	37	555	8.7
CHFA372	46661	358 (36)	51	39	189	136	51	255	6.9
CHFA376	46662	358 (36)	153	39	327	136	51	765	12.0
CHFA504	47733	508 (52)	104	51	276	160	74	740	14.7
CHFA673	46681	659 (67)	77	54	250	185	95	710	18.0
CHFA674	50830	659 (67)	102	54	277	185	95	950	19.5
CHFA676	46682	659 (67)	153	54	350	185	95	1425	25.0
CHFA1003	46701	1010 (103)	77	66	284	227	147	1100	29.0
CHFA1006	46702	1010 (103)	153	66	391	227	147	2205	40.0

