



- » Kapasite ton 29 - 220 tn
- » Kapasite k.N 290 - 2.200 k.N
- » Saplama metrik ölçü M24 – M64
- » Saplama inç ölçü 1" - 2.1/2"
- » Hidrolik Piston kursu 8 - 12 mm
- » Tek kademe çok kademe seçenekli
- » Yay dönüslü 1500 bar hidrolik sistem
- » Dar bölgelerdeki gerdirmelere uygun
- » Rüzgar trübini montajına uygun yapı
- » Siemens, Gamesa, GE, Nordex onaylı
- » Menşei İngiltere, Boltight -Nord Lock
- » Türkiye'de servis ve yedek parça hizmeti
- » Tensioning capacity ton 29 - 220
- » Tensioning capacity k.N 288 - 2.200
- » Compatible with metric bolts M24 - M64
- » Compatible with imperial bolts 1" - 2.1/2"
- » Stroke range from 8 mm up to 12 mm
- » Fitted with automatic piston retraction
- » Spring loaded gear driven nut rotation
- » Designed originally for wind energy market
- » Single or multi stage configuration available
- » Positive stop facility and cycle counter on option
- » Recomended by Siemens, Gamesa, Ge, Nordex
- » Origin England, made by Boltight Nord-Lock

Model Model	Parça Part	Kapasite Capacity		Dış Çap Out. Diameter	Saplama Ölçü Bolt Size		Stroke Stroke	Somun Nut A/F	Diş Adımı Pitch	Yükseklik Height
#	No.	Ton	k.N	mm	mm	inch	mm	mm	Yiv	mm
Typhoon Tek Kademeli Typhoon Single Stage	TTS-24	29	290	85	M24	1"	8	36	3.0	98
	TTS-27	37	375	91	M27	1.1/8"	8	41	3.0	104
	TTS-30	46	460	98	M30	1.1/8"	8	46	3.0	107
	TTS-33	57	570	109	M33	1.1/4"	8	50	3.5	115
	TTS-36	67	670	114	M36	1.3/8"	8	55	4.0	118
	TTS-39	80	800	128	M39	1.1/2"	10	60	4.0	124
	TTS-42	92	920	132	M42	1.5/8"	10	65	4.5	132
	TTS-45	108	1.080	142	M45	1.3/4"	10	70	4.5	134
	TTS-48	122	1.220	151	M48	1.7/8"	10	75	5.0	138
	TTS-52	145	1.450	162	M52	2"	10	80	5.0	140
	TTS-56	167	1.675	171	M56	2.1/4"	10	85	5.5	150
	TTS-64	220	2.200	182	M64	2.1/2"	12	95	6.0	162

