

Typhoon

BOLTIGHT™
PART OF THE NORD-LOCK GROUP



HİDROLİK SAPLAMA GERDİRME



Çoklu Kademe Hidrolik Saplama Gerdirmeler - [29 - 224 ton] Multi Stage Hydraulic Bolt Tensioner - [288 - 2244 k.N] - [M24 - M64]

- » Kapasite ton 29 - 224 tn
- » Kapasite k.N 288 - 2.244 k.N
- » Saplama metrik ölçü M24 - M64
- » Saplama inç ölçü 1" - 2.1/2"
- » Hidrolik piston kursu 7 - 12 mm
- » Tek kademe çoklu kademe seçenekli
- » Yay dönüslü 1500 bar hidrolik sistem
- » Dar bölgelerdeki gerdirmelere uygun
- » Rüzgar trübini montajına uygun yapı
- » Siemens, Gamesa, GE, Nordex onaylı
- » Menşei İngiltere, Boltight -Nord Lock
- » Türkiye'de servis ve yedek parça hizmeti
- » Tensioning capacity ton 29 - 224
- » Tensioning capacity k.N 288 - 2.244
- » Compatible with metric bolts M24 - M64
- » Compatible with imperial bolts 1" - 2.1/2"
- » Stroke range from 7 mm up to 12 mm
- » Fitted with automatic piston retraction
- » Spring loaded gear driven nut rotation
- » Designed originally for wind energy market
- » Single or multi stage configuration available
- » Positive stop facility and cycle counter on option
- » Recomended by Siemens, Gamesa, Ge, Nordex
- » Origin England, made by Boltight Nord-Lock

Model Model	Parça Part	Kapasite Capacity		Dış Çap Out. Diameter	Saplama Ölçü Bolt Size		Stroke Stroke	Somun Nut A/F	Diş Adımı Pitch	Yükseklik Height
#	No.	Ton	k.N	mm	mm	inch	mm	mm	Yiv	mm
Typhoon Çoklu Kademe Typhoon Multi Stage	TTM-24	29	288	60	M24	1"	7	36	3.0	185
	TTM-27	37	375	66	M27	1.1/8"	7	41	3.0	193.5
	TTM-30	46	462	72	M30	1.1/8"	7	46	3.0	201
	TTM-33	57	572	78	M33	1.1/4"	8	50	3.5	216
	TTM-36	67	670	82.5	M36	1.3/8"	10	55	4.0	229.5
	TTM-39	80	802	92	M39	1.1/2"	10	60	4.0	263
	TTM-42	92	920	98	M42	1.5/8"	10	65	4.5	262
	TTM-45	108	1.082	105	M45	1.3/4"	10	70	4.5	281.5
	TTM-48	122	1.222	111	M48	1.7/8"	10	75	5.0	293.5
	TTM-52	145	1.452	120	M52	2"	10	80	5.0	327
	TTM-56	167	1.675	128	M56	2.1/4"	10	85	5.5	330
	TTM-64	224	2.244	146	M64	2.1/2"	12	95	6.0	376

