



PTM Serisi Standart Havalı Tork Anahtarları - [100 - 6.000 N.m]

PTM Series Pneumatic Torque Wrenches - [100 - 6.000 N.m]



- » Torklama hassasiyeti $\pm 5\%$
 - » Minimum tork kapasitesi 100 N.m
 - » 6.000 N.m kadar 10 farklı model
 - » Sıkma ve sökme işlemlerine uygun yapı
 - » Boşta, yüksüz dönüş hızı 224 devir dakika
 - » Yumuşak başlatma, tetik ile kademeli hız ayarı
 - » Vites kutusu tutma kolundan bağımsız döner
 - » Sessiz (85db) , darbesiz çalışma, hızlı torklama
 - » Hedeflenen tork değerine ulaştığı zaman durur
 - » Norbar fabrika kalibrasyon belgesiyle sevk edilir
-
- » Accuracy up to $\pm 5\%$
 - » Minimum torque 100 N.m
 - » Maximum torque 6.000 N.m
 - » Clockwise and counterclockwise operation
 - » Free speed of 224 rpm for rapid bolt run-down
 - » 'Soft Start' allows gradual and safe reaction location
 - » Gearbox can rotate independently from the handle
 - » Quiet - less than 85 dB(A) when under load
 - » Clear indication of successful joint application
 - » Supplied with Norbar house calibration certificate

Parça Part	Tork Aralığı Torque Range		Kare Sürücü Square Drive	Devir Hızı Output Speed	Ağırlık Weight	Ölçüler (mm) Sizes							
	N.m	lbf.ft				inch	rpm	kg	D	H1	H2	H3	L
18100.B06	100 - 500	74 - 370	3/4"	224	5.0	52	29	224	116	310	59	71	131
18101.B06	160 - 800	118 - 590	3/4"	148	5.0	52	29	224	116	310	59	71	131
18102.B06	200 - 1.000	147 - 738	3/4"	122	6.8	72	29	224	116	342	68	91	165
18103.B08	270 - 1.350	200 - 1.000	1"	86	6.8	72	29	224	116	342	68	91	165
18104.B08	400 - 2.000	295 - 1.475	1"	58	7.2	72	29	224	116	371	74	91	165
180296.B08	540 - 2.700	400 - 2.000	1"	40	8.9	80	29	224	116	335	80	91	165
18159.B08	800 - 4.000	590 - 2.950	1"	32	9.9	92	29	224	116	394	87	115	205
18159.B12	800 - 4.000	590 - 2.950	1.1/2"	32	9.9	92	29	224	116	394	87	115	205
18108.B12	900 - 4.500	660 - 3.300	1.1/2"	23	15.5	119	29	224	116	415	118	150	199
18109.B12	1.200 - 6.000	885 - 4.500	1.1/2"	15.5	15.5	119	29	224	116	415	118	150	199

Verilen ağırlık destek ayağı ile olan toplam ağırlıktır. / The weight is total weight with reaction.

