



Açılı Tip Havalı Tork Anahtarları - [40 - 12.000 N.m]

Angled Pneumatic Torque Wrenches - [40 - 12.000 N.m]



- » Torklama hassasiyeti $\pm 5\%$
- » Minimum tork kapasitesi 40 N.m
- » 12.000 N.m kadar 8 farklı model
- » Sıkma ve sökme işlemlerine uygun yapı
- » İki vitesli yapı, hızlı ve yavaş torklama imkanı
- » Vites kutusu tutma kolundan bağımsız döner
- » Sessiz ve titreşimsiz çalışma ile ergonomik
- » Hedeflenen tork değerine ulaştığında durur
- » Cihaz fabrika kalibrasyon belgesiyle sevk edilir
- » Türkiye'de tamir bakım kalibrasyon hizmeti

- » Accuracy up to $\pm 5\%$
- » Minimum torque 40 N.m
- » Maximum torque 12.000 N.m
- » Clockwise and counterclockwise operation
- » 2 speed gearbox for slow and fast operations
- » Device have a 360°-rotatable pistol grip
- » Operate vibration-free and quietly, ergonomics
- » Tool stops when selected torque value reached
- » Supplied with house calibration certificate

Parça Part	Model Model	Tork Aralığı Torque Range	Kare Sürücü (A) Square Drive	Devir Hızı Output Speed	Ağırlık Weight	Ölçüler (mm) Sizes		
No.	#	N.m	inch	rpm	kg	D	H	C
57 084 000	TLW-84	40 - 880	3/4" - 1"	19	6	88	360	55/75
57 104 000	TLW-104	40 - 1.200	1"	19	7	88	360	75
57 244 000	TLW-244	70 - 2.500	1"	7.5	7	88	410	75
57 354 000	TLW-354	70 - 4.000	1.1/2"	7.5	8	88	410	95
57 504 000	TLW-504	100 - 5.000	1.1/2"	2	9	88	460	95
57 604 000	TLW-604	400 - 6.000	1.1/2"	2.8	12	130	420	110
57 904 000	TLW-904	450 - 10.000	1.1/2"	1.8	16	130	460	110
57 913 000	TLW-1205	600 - 12.000	1.1/2"	1.8	18	175	470	115

