



- » Torklama hassasiyeti  $\pm 3\%$
  - » Tork aralığı 20- 3000 N.m
  - » Tork aralığı 15- 750 Lbf.ft
  - » 1/2", 3/4" , 1" ve 1.1/2" kare sürücülü
  - » Çift skalalı tasarımla iki birimde çalışma
  - » Arttırılabilir kol uzunluğu ile daha az efor
  - » Ayarlanan torka ulaştığında klik sesiyle uyarı
  - » Ağır sanayi şartları için uygun dizayna sahip
  - » Seri numaralı üretici fabrika kalibrasyon belgesi
  - » ISO 6789-B107.300-2010ye uygun tasarım
  - » Menşei Tayvan, Markası Torc-Tech , CE sertifikalı
  - » Servis ve kalibrasyon Surkon tarafından karşılanır
- 
- » Torque accuracy  $\pm 3\%$
  - » Torque ranges 20 - 3000 N.m
  - » Torque ranges 15 - 740 Lbf.ft
  - » 1", 3/4" , 1" and 1.1/2" square drive
  - » Meets the requirements of ISO 6789
  - » Dual-scales window (N.m. & Ft-lb)
  - » Loud click sound when torque value reached.
  - » Supplied with a Declaration of Conformance
  - » Delivered with house calibration certificate
  - » Origin Taiwan, manufactured by Torc-Tech, CE certified

Parça Part	Tork Aralığı Torque Range		Sürücü Sq. Drive	Hassiyet Accuracy	Ölçek Graduation	Boy Lenght	Ağırlık Weight
	N.m	lbf.ft					
TW0212	20 - 120	15 - 90	1/2"	$\pm 3\%$	5	475	1.3
TW0420	40 - 200	30 - 150	1/2"	$\pm 3\%$	5	563	1.5
TW0530	50 - 300	35 - 220	1/2"	$\pm 3\%$	5	625	1.7
TW1155	110 - 550	80 - 400	3/4"	$\pm 3\%$	10	827	3.0
TW1476	140 - 760	100 - 560	3/4"	$\pm 3\%$	10	827	3.0
TW2010	200 - 1.000	140 - 740	3/4"	$\pm 3\%$	10	1413	3.8
TW6015	600 - 1.500	*	1"	$\pm 3\%$	25	1615	10.9
TW7520	750 - 2.000	*	1"	$\pm 3\%$	50	2370	11.7
TW1530	1.500 - 3.000	*	1.1/2"	$\pm 3\%$	50	2820	16.4



Kolay Ayar ve Kilit Mekanizması



Tork Değeri Kol Tutuşundan Etkilenmez

